

# Pioneer DVD Player DVD-V7300D

DVD-V7300D - Industrial DVD-Video player

| <b>Specifications</b>                     | <b>DVD-V7300D</b>  |
|---|--|
| Regional code                             | 2  |
| Power Requirement                         | 220V-240V 50-60Hz  |
| Power connector type                      | UK and Euro type figure 8                                |
| Power consumption                         | 15 Watt  |
| Power consumption in standby mode         | 1 Watt   |
| Dimensions                                | 210(W)×119(H)×412(D) mm                                  |
| Weight                                    | 4,5 kg   |
| Remote Control Unit                       | CU-V162  |
| Operating temperature                     | 5°-35°   |
| Operating humidity                        | Less than 85 %   |
| Video Signal Type                         | PAL, NTSC  |
| External synchronizing input signal level | Black burst - 0,3 Vp-p/ (75 ohm), BNC x 2 (loop through) |
| Playable Format                           | DVD-Video & Video-CD (PAL,NTSC), Audio CD (CD-DA)        |
| Playable Disc                             | DVD-Video, Video-CD, CD-DA, DVD-R, CD-R (not DVD-RAM)    |
| Composite Video Output                    | 1 Vp-p / (75ohm)   |
| S2-Video Y Output level                   | 1 Vp-p / (75ohm)   |
| S2-Video C Output level                   | 286mVp-p / (75ohm)                                       |
| Component Video Y output level            | 1 Vp-p / (75ohm)   |
| Component Video Cb output level           | 0,7Vp-p / (75ohm)  |
| Component Video Cr output level           | 0,7Vp-p / (75ohm)  |
| S/N ratio                                 | more than 60 dB  |
| Horizontal resolution                     | more than 500 lines                                      |
| Audio Output                              | 200 mVrms (1kHz, -20dB)                                  |
| Number of channels                        | 2  |
| Frequency response                        | 4Hz- 22kHz (DVD fs : 48kHz) - 4 Hz-22kHz (CD)            |
| S/N ratio                                 | 115 dB   |
| Dynamic range                             | 97 dB  |
| Composite Video Out                       | 1 x BNC, 1 x RCA   |
| S-Video Out                               | 1 x S2   |
| Component Out                             | 1 x BNC( Y,Cb,Cr)  |
| Audio Out (Analog)                        | 1 x RCA (L/R), 1 x RCA (Mono)                            |
| Audio Out (Digital Coaxial)               | 1 x RCA (AC-3/PCM/DTS)                                   |
| AUTO/PAL/NTSC select switch               | 1  |
| External sync terminal                    | 2 x BNC (loop through)                                   |
| Interface connector (RS-232C)             | 1 x (D-SUB 15pin)  |
| Composite/Component select SW             | 1  |
| Signal GND terminal                       | 1  |